DESK MASTER STATION



when communication is critical

FEATURES

- Combined wall and desk master station with full access to all features in STENTOFON AlphaCom E exchange
- 10 programmable single touch keys with name tags
- Handset for confidential conversation
- Selectable private / open mode
- Electret microphone with automatic sensitivity adjustment
- 1W loudspeaker



This combined desk top and wall mount master station gives full access to all features in the STENTOFON AlphaCom E exchange. The station includes both programmable single touch keys and a handset for confidential conversations. The station is also equipped with a private / open switch for choosing between direct incoming calls and announcement of calls by a ringing tone. An 1W (63 Ohm) loudspeaker is provided along with a volume control bar.

Further, the station's electret microphone automatically adjusts its sensitivity according to the input level. When in conversation, the station's red lamp lights to indicate that the microphone is live. The station must be provided with a cable for connection to a wall socket. Alternative cable lengths and wall plugs are available (see next page). Required cable must be ordered separately. A bracket is included for wall mounting of the station.

Two pair twisted telephone cable (0.5 mmø / 24 AWG) is required between the exchange and the station, which can be positioned up to 1400 meters / 4600 feet away from the exchange (maximum 240 0hm loop resistance). Longer distances are possible with heavier wires.

SPECIFICATIONS

Order Number	1007034210
Operation Voltage	Powered from exchange
Cable Requirements	2 pair twisted cable 0.5 mm2 / 24 AWG. (Max. loop resistance 240 0hm)
Temperature Range	0° C to +40° C +32° F to +104° F
Humidity Range	10% - 85% RH (non condensing)
Dimensions: (W x H x D)	225 mm x 75 mm x 176 mm 8.86" x 2.95" x 6.93"
Finish	Grey/Black ABS Plastic with structure, MT 1055




sales@ringuk.com 01353 865568

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1007034210 Supplementary	Desk Master Station	0.685 kg/1 lb 8 oz
equipment: EPKAB 98510 EPKAB 98515	StationCable, 3 meters / 10 feet, modular jack plug StationCable, 0.5 meter / 20 inches, modular jack plug	50 g / 2 oz 50 g / 2 oz


DESKMASTERSTATION

Loudspeaker Output	1 W (63 Ohm)
Loudspeaker Impedance	63 Ohm
Frequency Range	300 - 5000 Hz
Microphone Output Voltage Microphon B reamp.	100/300 mV 1000 Ohm
Wall SocketConnector Type	Modular jack
Indicator	LED (red)

WIRING




PINCONFIGRATION



STATIONDRAWING





ORDER NUMBER DOC NO 1007034210 A100K10022 v.2.0

sales@ringuk.com



STENTOFON products are developed and marketed by Zenitel Norway AS. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001:2002. ZENITEL NORWAY AS reserves the right to mo designs and alter specifications without prior notice, in pursuance of a policy of continuous improvement. © 2009 Zenitel Norway AS.