zenitel
because communication is critical

1008140100

TA-10

Relay Module

ICX-AlphaCom

Exigo

DESCRIPTION

- Designed for use with Turbine Industrial IP Intercom stations
- Dual high-power relays (DPDT)
- Up to 400VAC /48 VDC per relay
- Up to 6A current per relay
- Heavy-duty spring-loaded terminals with spare grounding terminals
- Powered by Turbine Industrial stations (TFIE-x) or Turbine Extended Kit (TKIE-1)

The TA-10 is a 2x DPDT, high-power relay module for the TFIE family of Turbine Industrial stations and the TKIE kit. It may also be used with the EAPII series access panels for the Exigo PA/GA system.

www.ringuk.com   sales@ringuk.com

SPECIFICATIONS

MECHANICAL

Dimensions (WxDxH)	100 x 50 x 40 mm
Weight	100 g

ENVIRONMENTAL

Operational Temperature	-40°C to + 70°C
Storage Temperature	-40°C to +70°C
Ingress Protection (IP)	N/A
Impact Protection (IK)	N/A

ELECTRICAL

Drive Voltage	12V (from Turbine Extended)
Switched Voltage	< 250VAC Rated (400VAC Max)
Switched Voltage	< 2000 VA max
Switching Current	< 8A rated (15A max, 4s)

USED WITH

1023201206
EAPII-6

Exigo Industrial Access Panel, 6 Buttons

1023201201
EAPII-1

Exigo Industrial Access Panel, 1 Button

1008122010
TFIE-1

IP and SIP Intercom

1008122020
TFIE-2

IP and SIP Intercom

www.ringuk.com   sales@ringuk.com

1008122060

TFIE-6

IP and SIP Intercom

www.ringuk.com   sales@ringuk.com